

Typ	Szerokość	Podziałka	System prowadzenia	Wzór bieżnika	Rozmiary						Maksymalna masa maszyny	Ciężar na ogniwo
	mm	mm			1	2	3	4	5	6	kg	kg
konwencjonalny	150	72	A	1	65	46	39	23	23	21	500	0,51
	180	60	B	2	61	54	32	25	20	22	500	0,60
	180	72	A	3	70	51	38	24	29	30	700	0,69
	180	72K	K	4	64	53	40	21	22	20	700	0,91
	190	72	A	5	68	50	38	21	28	27	800	0,70
	200	72	A-B	5	76	56	40	23	28	26	1200	0,90
	200	72K	K	6	71	53	39	23	30	29	1200	1,09
	230	72	A	7	82	57	40	24	30	26	1400	1,23
	250	72	A-B	7	82	57	40	24	30	26	1600	1,32
	280	72	A-B	12	73	59	38	25	28	25	2600	1,50
	320	84	K	18	96	82	60	46	48	34	4500	3,25
	320	86	K	12 - 18	84	69	51	37	43	29	3850	3,32
	320	90	B	19	86	65	47	32	50	35	3000	2,40
	320	100	B	17	76	54	39	26	30	25	3200	2,50
	350	90	B	24	76	46	35	24	41	40	3500	1,80
	400	90	B	24	82	68	52	38	35	32	5000	2,36
	420	100	B	19	96	86	64	50	52	36	5000	5,44
	450	84	K	12 - 18	96	81	65	45	47	33	7000	5,40
	450	86	K	12 - 18	97	82	66	48	48	36	6900	4,90
	450	100	K	18	100	78	64	44	50	41	8000	5,65
500	90	F	19	94	82	62	42	51	36	6500	5,73	
Wymienny (długi)	230	96	C	8	73	63	30	25	23	23	1500	1,78
	250	96K	K	4	70	60	30	25	20	19	2000	2,20
	260	96	K	11	70	64	32	27	22	20	2100	2,20
	260	109N	C-D	4	84	76	36	31	24	30	2500	2,82
	280	106Y	K	1	80	72	36	30	28	28	3000	3,30
	300	109K	K	13	82	78	34	29	23	27	3500	3,26
	300	109N	C-D	14	82	65	35	29	27	28	3500	3,10
	300	109W	C-D	8	92	80	44	36	27	28	3500	3,95
	320	106Y	K	8	79	71	36	30	26	27	3600	3,70
	350	108W	C-D	4	90	84	44	40	25	14	3500	4,08
	350	109W	C-D	5	92	84	44	40	26	20	3500	4,23
	370	107K	K	11	94	86	42	38	26	28	4000	4,80
	400	107K	K	11	90	83	43	38	27	25	4800	5,25
	400	142K	K	11 - 13	87	81	32	28	34	27	5000	7,45
	400	144Y	K	11	126	90	44	35	30	26	5000	8,74
450	163K	K	11	110	104	50	38	27	28	8500	12,06	
Wymienne	230	48	C	1	72	66	32	24	24	25	1500	0,94
	250	47K	K	16	68	61	30	25	25	21	1600	1,06
	250	48,5Y	K	9	66	60	29	24	21	20	1600	1,18
	250	52,5K	K	10	81	74	33	26	25	25	1550	1,34
	250	52,5N	C-D	14	86	74	40	30	23	21	1550	1,29
	300	55	C-D	1	82	72	36	29	26	28	4000	2,03
	300	52,5K	K	15	84	77	35	29	27	26	3500	1,88
	300	52,5N	C-D	16	82	74	39	30	23	16	3500	1,87
	300	52,5W	C-D	14	96	82	48	43	22	23	3500	1,87
	300	52,5WK	K	1	92	84	46	40	24	24	3500	1,88
	300	53K	K	1	88	79	35	31	25	19	3500	1,94
	300	55,5Y	K	9	80	76	36	32	22	27	4000	2,13
	320	54	C-D	4	80	72	40	29	23	21	3600	1,96
	350	56	C-D	1	90	85	47	39	25	16	3500	2,20
	350	52,5W	C-D	14	94	84	48	42	22	19	4000	2,01
	350	54,5K	K	20	92	87	44	40	23	22	4000	2,40
	350	75,5Y	K	9	98	85	45	38	23	25	3500	3,35
	400	72,5K	K	21	94	82	44	38	29	26	6000	4,35
	400	72,5KB	K	10	94	80	49	37	24	26	6000	3,42
	400	72,5KU	K	1	112	98	55	46	24	25	6000	3,50
	400	72,5N	C-D	1 - 22	100	86	44	38	26	24	6000	3,63
	400	72,5W	C-D	14 - 23	108	99	56	51	26	24	6000	3,89
	400	72,5Y	K	22	86	73	38	28	30	24	6000	3,75
	400	74N	C-D	15	100	88	46	38	25	29	5800	3,46
	400	75,5Y	K	9	100	94	45	38	24	24	4500	4,06
	450	71	C-D	14	115	106	47	42	29	17	7000	5,07
	450	73,5	C-D	1	118	106	50	42	31	34	7100	4,95
	450	76	C-D	1	122	109	60	48	30	31	7300	5,41
	450	81N	C-D	14 - 16	112	103	52	38	25	23	7300	5,19
	450	81W	C-D	1	140	128	66	58	29	33	7500	5,25
450	83,5K	K	16	112	100	52	42	24	25	8000	5,85	
450	83,5Y	K	9	113	102	52	38	24	27	8000	5,83	
500	92N	C-D	16	130	116	66	48	27	27	12000	8,05	
500	92W	C-D	16	158	145	71	62	30	34	12000	8,30	